

Declare. SM

SUPAFIL® (Loft, Thermoloft, Optiloft, Cavity, Timber Frame, Max Frame, CarbonPlus & Spray Blowing Wool) Knauf Insulation

Final Assembly: Multiple Locations in Europe

Life Expectancy: Life of structure Year(s)

End of Life Options: Salvageable/Reusable in its Entirety,
Landfill

Ingredients:

Glass mineral wool: EC: 926-099-9 Man-Made Vitreous (silicate) Fibers; **Silicone:** Siloxanes and Silicones, Me-H; **Dust Oil:** Distillates (petroleum), solvent-dewaxed light paraffinic; **Antistatic Agent:** Quaternary ammonium compounds, alkyl phosphate potassium salt, Et sulfates

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: AgBB Scheme French A+ 2011

I-14 Responsible Sourcing: Not Applicable

KNF-0040

EXP. 01 NOV 2021

Original Issue Date: 2020